



ahead of the curve®

Masterclass.

“Subwoofers of the Gods”

– Chris Martens, *The Perfect Vision*, February 2007




Editors' Choice

– 2008, 2009, 2010, 2011, 2012 & 2013, *The Absolute Sound*

“What are they, exactly? I can’t answer that in a nutshell. Not if you want more specific than fantastic. The condensed version is that they are relatively small, insanely well-built, extremely powerful, very smooth, tight, detailed to a fine line, clean, poised, dynamically proficient, utterly kick-ass subwoofers.”

– Colin Miller, *Secrets of Home Theater and High Fidelity*



FATHOM® f112v2

The challenges associated with designing high-output, compact subwoofer systems can be daunting. In most cases, designers sacrifice low-frequency extension or output capability in order to keep a design acceptably small.

The Fathom® subwoofers sacrifice nothing, thanks to the dynamic advantages of their proprietary JL Audio drivers. These exceptional woofers allow for a true subwoofer passband and very high output, while keeping distortion well below audible thresholds. To extract full benefit from the excursion envelope of its woofer design, each Fathom® employs an uncommonly powerful switching amplifier with a large toroidal transformer and a patented circuit, designed to enhance control and fidelity.

The compact design and conventional form factor of the Fathoms apply beautifully to most home theater applications, including built-in designs. Front-mounted controls make them comfortable to set up and adjust, while JL Audio’s powerful DSP engine and exclusive Digital Automatic Room Optimization makes sure that response is smooth, even in challenging rooms.

While very compact, the f112v2 is powerful enough to anchor serious home theater setups and is equally at home in the most critical music listening applications. For that very reason, it is used in some of the best recording and mastering studios in the world.

Fathom® f112v2 Features:

Unbalanced Inputs:

Stereo or Mono (two RCA jacks)

Balanced Inputs:

Stereo or Mono (two female XLR jacks)

Output To Slave:

Balanced (one male XLR jack)

Input Modes:

Master or Slave

Level Modes:

Reference (fixed gain) or Variable from full mute to +15 dB over reference gain

Power Modes:

Off, On or Automatic Signal-Sensing

Light Modes:

Off, On or Dim

Low Pass Filter Mode:

Off, 12 dB per octave or 24 dB per octave

Low Pass Filter Crossover Frequency:

Variable from 30 Hz – 130 Hz

Polarity:

0 or 180 degrees

Phase:

Variable from 0 – 280 degrees, referenced to 80 Hz

E.L.F. Trim:

Variable from -12 dB to +3 dB at 25 Hz

Digital Automatic Room Optimization (D.A.R.O.):

18-Band, with included, laboratory-grade calibration microphone, defeatable

Fathom® f112v2 Specifications:

Enclosure Type:

Sealed

Driver:

Single 12-inch (nominal diameter)

Frequency Response: (anechoic)

21 – 119 Hz (± 1.5 dB)
 -3 dB at 19 Hz / 150 Hz
 -10 dB at 17 Hz / 167 Hz

Effective Piston Area:

84 sq. in. (0.0542 sq. m)

Effective Displacement:

287 cu. in. (4.7 liters)

Amplifier Power:

1.8 kW RMS short-term

Dimensions* (H x W x D):

18.50 in. x 15.0625 in. x 17.75 in.
 470 mm x 384 mm x 451 mm

Net Weight:



100 lbs. (45 kg)

Cabinet Finish:

High-Gloss Black

Built in USA

with imported and domestic components



* All height dimensions include feet, depth dimensions include grilles.



"JL Audio", "Ahead of the Curve", "Gotham", "Fathom" and the JL Audio logo are registered trademarks of JL Audio, Inc.
 ©2015 JL Audio, Inc. • U.S. PATENTS: #5,734,734 #5,949,898 #6,118,884 #6,229,902 #6,243,479 #6,294,959 #6,501,844 #6,496,590 #6,441,685 #5,687,247 #6,219,431 #6,625,292
 #D472,891 #D480,709 Other U.S. & Foreign patents pending. Due to our policy of continuous product development, all specifications are subject to change without notice.

www.jlaudio.com

10369 North Commerce Parkway • Miramar, Florida • 33025 • USA



SKU#97273 10-2015

Printed in U.S.A.